



Kvalitet: **404**
Quality:

oo1 Hvit/*White*

Kvalitet: **404**
Quality:

Tekniske Spesifikasjoner/Technical Characteristics

Vev <i>Base fabric</i>		Polyester, 1100 dtex
Belegg <i>Coating</i>		PVC
Tråder per cm <i>Threads per cm</i>		4,3 x 4,3
Bredde <i>Width</i>	EN 1848-2	204 cm
Vekt <i>Weight</i>	EN 1849-2	550 g/m ²
Rivestyrke <i>Tear resistance</i>	EN 12310-2/	280/280 N
Strekstyrke <i>Tensile strength</i>	EN 12311-2	1650/1500 N/5cm
Adhesjon <i>Adhesion</i>	DIN 53357	80 N/5 cm
Flammemotstand <i>Flame retardancy</i>	ISO 11925-2	B-s3,d0
Temperaturbestandighet <i>Temperature resistance</i>	EN 495-5/DIN 53361	+ 70 °C - 30 °C

De oppgitte verdiene er gjennomsnittsverdier fra produksjonen. Vi forbeholder oss retten til endringer uten varsel.
Technical values are average values from the production. The information may change at any time without prior notice.

Eksempler på bruksområde: Innerduk haller, små telt
Suitable applications: Inner skin soft skinned buildings, tents

Kvalitet: **404**
Quality:



Godkjenninger:
Approvals:

Produkt/Product:	Godkjent av/Approved by:
Kvalitet: 404 Quality:	SINTEF Produktdokumentasjon Nr. Sintef EA-133 Documentation No. Sintef EA-133 SITAC Typgodkännandebevis 2935/81 Swedish Technical Approval 2935/81 ETA Godkendelse MK 6.10/0573 Approval MK 6.10/0573

