

Kvalitet: **453**
Quality:



118 Rød/Red
NSC kode/NCS Code: 1080-Y90R

Kvalitet: **453**
Quality:


Tekniske Spesifikasjoner/Technical Characteristics

Vev <i>Base fabric</i>		Polyester, 1100 dtex, 2-skaft
Belegg <i>Coating</i>		PVC
Bredde <i>Width</i>	EN 1848-2	204 cm
Vekt <i>Weight</i>	EN 1849-2	700 g/m ²
Rivestyrke <i>Tear resistance</i>	DIN 53356	425/400N
Strekstyrke <i>Tensile strength</i>	EN 12311-2	3000/2900 N/5 cm
Adhesjon <i>Adhesion</i>	DIN 53357	100 N/5 cm
Flammemotstand <i>Flame retardancy</i>	ISO 11925-2	B-s3, d0
Temperaturbestandighet <i>Temperature resistance</i>	EN 495-5/DIN 53361	+ 70 °C - 30 °C


De oppgitte verdiene er gjennomsnittsverdier fra produksjonen. Vi forbeholder oss retten til endringer uten varsel.
Technical values are average values from the production. The information may change at any time without prior notice.

Eksempler på bruksområde:
Suitable applications:


Haller, flat-presenning, draperier
Soft skin buildings, flat tarpaulins, industrial room dividers




991 – Grå/Grey
 NSC kode/NCS code: 2000



664 – Blå/Blue
 NSC kode/NCS code: 3060-R90B



001 – Hvit/White



442 – Grønn/Green
 NCS kode/NCS code: 6020-B90G



118 Rød/Red
 NSC kode/NCS Code: 1080-Y90R

Kvalitet: **453**
Quality:



Godkjenninger:
Approvals:

Produkt/Product:	Godkjent av/Approved by:
Kvalitet: 453 Quality:	SINTEF Produktdokumentasjon Nr. Sintef EA-133 Documentation No. Sintef EA-133 SITAC Typgodkännande 2935/81 Swedish Technical Approval 2935/81 ETA Godkendelse MK 6.10/0573 Approval MK 6.10/0573

