



Kvalitet: **753 Lakkert/Laquered**  
Quality:

**Kvalitet:** **753 Lakkert/Laquered**  
**Quality:**

Tekniske Spesifikasjoner/Technical Characteristics		
Vev <i>Base fabric</i>		Polyester, 1100 dtex, 2-skaft
Belegg <i>Coating</i>		PVC
Bredde <i>Width</i>	EN 1848-2	204 cm
Vekt <i>Weight</i>	EN 1849-2	700 g/m <sup>2</sup>
Rivestyrke <i>Tear resistance</i>	DIN 53356	425/400 N
Strekstyrke <i>Tensile strength</i>	EN 12311-2	3000/2900 N/5cm
Adhesjon <i>Adhesion</i>	DIN 53357	100 N/5 cm
Flammemotstand <i>Flame retardancy</i>	ISO 11925-2	B-s3, d0
Temperaturbestandighet <i>Temperature resistance</i>	EN 495-5/DIN 53361	+ 70 °C - 30 °C

De oppgitte verdiene er gjennomsnittsverdier fra produksjonen. Vi forbeholder oss retten til endringer uten varsel.  
*Technical values are average values from the production. The information may change at any time without prior notice.*

Eksempler på bruksområde: **Haller, structure**  
*Suitable applications:* **Soft skin buildings, structures**

991 – Grå/Grey  
 NSC kode/NCS code: 2000

664 – Blå/Blue  
 NSC kode/NCS code: 3060-R90B

001 – Hvit/White

442 – Grønn/Green  
 NCS kode/NCS code: 6020-B90G

Kvalitet:  
Quality:

## 753 Lakkert/Laquered



**Godkjenninger:**  
**Approvals:**

Produkt/Product:	Godkjent av/Approved by:
Kvalitet: <b>753</b> Quality:	SINTEF Produktdokumentasjon Nr. Sintef EA-133 <i>Documentation No. Sintef EA-133</i>  SITAC Typgodkännandebevis 2935/81 <i>Swedish Technical Approval 2935/81</i>  ETA Godkendelse MK6.10/0573 <i>Approval MK 6.10/0573</i>  MPA NPW P-MPA-E-06-517 <i>Baustoffklasse B1(DIN 4102-01, 05/98)</i>

