



Kvalitet: **780 Lakkert/Laquered**
Quality:

442 Grønn/Green
NCS kode/NCS code:6020-B90G

Kvalitet: **780 Lakkert/Laquered**
Quality:

Tekniske Spesifikasjoner/Technical Characteristics		
Vev <i>Base fabric</i>		Polyester, 1100 dtex, 2/2 - panama
Belegg <i>Coating</i>		PVC
Bredde <i>Width</i>	EN 1848-2	204 cm
Vekt <i>Weight</i>	EN 1849-2	900 g/m ²
Rivestyrke <i>Tear resistance</i>	DIN 53356	1000/1000 N
Strekstyrke <i>Tensile strength</i>	EN 12311-2	3400/3400 N/5cm
Adhesjon <i>Adhesion</i>	DIN 53357	100 N/5 cm
Flammemotstand <i>Flame retardancy</i>	ISO 11925-2	B-s3, d0
Temperaturbestandighet <i>Temperature resistance</i>	EN 495-5/DIN 53361	+ 70 °C - 30 °C

De oppgitte verdiene er gjennomsnittsverdier fra produksjonen. Vi forbeholder oss retten til endringer uten varsel.
Technical values are average values from the production. The information may change at any time without prior notice.

Eksempler på bruksområde: **Haller**
Suitable applications: **Soft skin buildings, structures**

991 – Grå/Grey
 NSC kode/NCS code: 2000

664 – Blå/Blue
 NSC kode/NCS code: 3060-R90B

001 – Hvit/White

442 – Grønn/Green
 NCS kode/NCS code: 6020-B90G

118 Rød/Red
 NCS kode/NCS code: 1080-Y90R

Kvalitet:
Quality:

780 Lakkert/Laquered



Godkjenninger:
Approvals:

Produkt/Product:	Godkjent av/Approved by:
Kvalitet: 780 Quality:	SINTEF Produktdokumentasjon Nr. Sintef EA-133 Documentation No. Sintef EA-133 SITAC Typgodkännandebevis 2935/81 Swedish Technical Approval 2935/81 ETA Godkendelse MK6.10/0573 Approval MK 6.10/0573 MPA NPW P-MPA-E-06-516 Baustoffklasse B1(DIN 4102-01, 05/98)

